

SHIELD®

INDUSTRIAL



GI/104

Industrial Black Rubber Gauntlets Extra Long

1 pair

- DE** Gummi-Industriehandschuhe – Extra lang
- FR** Gants industriels en caoutchouc – Extra long
- ES** Guantes industriales de caucho – Extra largo
- NL** Rubber industrie handschoenen – Extra lang
- PT** Luvas industriais de caucho – Extra longo
- CS** Rukavice průmyslové gumové – Extra dlouhé
- PL** Rękawice przemysłowe gumowe – Bardzo długie
- SV** Skyddhandskar i naturgummi – Extra lång
- DA** Industri Gummi handsker – Ekstra lang
- FI** Kumi suojakäsineitä – Erikoispitkä
- NO** Korttidshansker i lateks – Ekstra lang
- RO** Mănuși industriale din cauciuc – Extra lung
- BG** Каучукови промишлени ръкавици – По-дълги
- AR** قفازات مطاطية الصناعية – اضافية طويلة


LOT

Made in: Sri Lanka



Category III



 **HPCHL, PO Box 85, SM4 9AW, UK.**

Industrial Glove User Information:

Compliant with the Personal Protective Equipment Directive 89/686/EEC and European Standard EN420: Protective Gloves. Classification: Category III. PPE type examination conducted by Inspec, Manchester, UK - notified body 0194.

EN374-3:

Permeation requirements necessitates a minimum level 2 performance for three chemicals tested from the list detailed in EN 374-1.

Should the glove meet this requirement then the fuming flask pictogram shall be used with the letter code of each chemical. Should the glove not meet this requirement then the beaker pictogram shall be used providing the glove meets the requirements of EN374-2 water proof gloves and low chemical resistance.

Performance	Chemical	Chemical Code	Performance level			
GI/104	Methanol	A	6			
	Sodium Hydroxide (40%)	K	6			
	Sulphuric Acid (40%)	L	3			
Requirement						
Performance Level	1	2	3	4	5	6
Breakthrough time (mins.)	> 10	> 30	> 60	> 120	> 240	> 480

EN388:

Protection against mechanical risks necessitates a minimum level 1 performance. The pictogram displays a hammer symbol with the performance level, the position of which represents the test:

GI/104: 4 0 1 1

- 4** Abrasion Resistance (level 0 minimum – 4 maximum)
- 0** Blade Cut Resistance (level 0 minimum – 5 maximum)
- 1** Tear Resistance (level 0 minimum – 4 maximum)
- 1** Puncture Resistance (level 0 minimum – 4 maximum)

Product Efficacy and Usage:

The physical properties of the Rubber Latex glove can be altered through the effects of storage (temperature, light and ozone exposure) and usage; they were tested under laboratory ambient conditions.

The gloves were tested in the palm area and the test performance levels were obtained on new unused gloves, therefore, the results are not valid for gloves that have been washed or regenerated.

The gloves provide protection against mechanical risk.

The gloves do not provide protection against cold

The gloves do not provide protection against heat

The gloves do not provide protection against electricity

The gloves should not be used after the expiry date printed on the box (three years following date of manufacture).

The gloves must not be used should the Rubber Latex material be cracked, hardened or display holes / tears.

Warning: The gloves should be stored in the original packaging, under normal temperature and humidity conditions as displayed on the outer carton and insert.

Warning: Contains natural rubber latex, which can cause allergic reactions, including anaphylactic responses.