MaxiDex

TYPELIST AND PERFORMANCE VALUES

FU Type Examination Certificate(s) issued by:

TÜV Rheinland LGA Products GmbH(i.d. 0197), Tillystraße 2, 90431 Nürnberg, Germany

Glove	Size	Harmonized Standards / Level
MaxiDex® 19-007	6-11	EN ISO 21420:2020 EN 388:2016+A1:2018 - 3111A EN ISO 374-2:2016 EN ISO 374-5:2016 - VIRUS

The PPE is subject to the conformity assessment procedure- Modul D- based on quality assurance of the production process under surveillance of the notified body: SGS FIMKO OY (0598) P.O.Box 30 (Särkiniementie 3), 00211 Helsinki, FINLAND

USE (MECHANICAL PROTECTION)

Liquidproof protective glove for mechanical work with additional protection against viruses and bacteria.

Mechanical performance values refer to the palm of the hand. Protection against viruses and bacteria applies to the entire glove.

WARNING

No protection against liquids or chemicals. Do not use these gloves to protect against serrated edges or blades or naked flames. The gloves shall not be worn when there is a risk of entanglement by moving parts or machines.

The glove is liquid/air proof according to EN ISO 374-2, but is not designed for handling hazardous chemicals. It protects against the penetration of water, sweat and the penetration of hacteria and / or viruses

The resistance to liquids (penetration) was assessed on samples under laboratory conditions and relates only to these samples. It is recommended to check whether the gloves are suitable for the intended use, as the conditions at the workplace, depending on temperature and abrasion, can deviate from those of the type test

Donning: Wash and dry your hands completely before donning the gloves. Before use, inspect the gloves for any defects or imperfections and avoid wearing damaged, heavily soiled, worn or dirty (also internally) glove of any substance, this could irritate and/or infect the skin and cause dermatitis. In this event, seek medical advice from the company doctor or consult a dermatologist. Ensure the gloves fit well. Doffing: When removing your gloves, place the fingertips into the palm of the other glove. Pull the glove until almost off, Repeat on the other hand. With both gloves almost off shake both hands to remove the gloves fully. After use, clean the gloves thoroughly with a dry cloth to remove any contaminants. If the gloves are to be reworn store in such a way that the inside lining of the support can dry out easily.

Alternatively, the gloves can be washed according to the care instructions in these recommendations for use. To ensure protection against viruses or bacteria, do not touch the outside of the glove when taking off.

For more information on glove selection, usage and performances please contact ATG® (info@atg-glovesolutions.com) or the supplier of these gloves.

EXPLANATION OF THE PICTOGRAMS

EN ISO 21420:2020

General requirements (risk category, sizing, marking, labelling, etc.)

Information supplied by the manufacturer in the user notice

EN 388:2016+A1:2018 Mechanical Hazards

A: Abrasion resistance - number of rubs (Level 0-4) B: Blade cut resistance - Coupe Test - Index (Level 0-5)

ABC DEF

C: Tear resistance - N (Level 0-4) D: Puncture resistance N (Level 0-4)

E: TDM Cut resistance according to ISO 13997 - N (Level A-F)

F: Impact protection according to EN 13594:2015 - Y/N (P=Yes)



EN ISO 374-5:2016

Protective gloves against microorganisms

Protective gloves which form a protective barrier to microbiological

agents. Protection against VIRUSES and BACTERIAS.

Higher values stand for better protection/resistance. If "X" is marked as a performance level the test is either not applicable or not proceeded. Puncture resistance should not be confused with piercing exerted by thin tips or needles.

CONSTITUANTS / ALLERGIES

Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately

SHOULD YOU REQUIRE MORE INFORMATION ABOUT POTENTIAL ALLERGIC SUBSTANCES WITH OUR GLOVES PLEASE CONTACT ATG® OR YOUR LOCAL DISTRIBUTER

CARE INSTRUCTIONS

Storage/Cleaning:

Store the gloves in their original packaging in a cool and dry place. Keep away from direct sunlight, heat, flame and sources of Ozone. Gloves can be laundered at 40°C with a standard detergent (3 cyles), Natural drying. The gloves should be checked for leaks.

Use the gloves within 3 years of their purchase date.

Disposal/Waste

Used gloves maybe contaminated with infectious or hazardous substances. Dispose of according to the Local Authority/Municipality Regulations, landfill or incinerate under controlled conditions.

WARRANTY/LIMITATION OF DAMAGES

ATG® warrants that this product shall be in accordance with ATG® standard specifications as of the date of delivery to authorized distributors. Except to the extent prohibited by law, this warranty is in line with all warranties, including any warranty of fitness for a particular purpose; ATG® liability shall be limited to the purchase price of the product at issue. Buyers and users of this product are deemed to have accepted the terms of this limitation of warranty, which may not be varied by any verbal or written agreement.

