

CUT RESISTANT SLEEVE FOR FULL ARM PROTECTION

Comfortable 22 inch cut resistant sleeve with a secure, adjustable fastening.

FEATURES

- › Full arm cut protection from wrist to shoulder
- › Cut resistant: Level D (EN 388:2016)
- › Lightweight - 13 gauge construction
- › Thinner material on palm and back of hand improves comfort and dexterity when combined with a glove
- › Adjustable VELCRO® Brand hook and loop fastening strap for a secure fit
- › Thumbhole prevents sleeve from rising up and exposing the wrist
- › Light thermal protection up to 100°C for a short period
- › Soft and comfortable to wear
- › Ambidextrous
- › Length: 22 inches (55cm)



SUITABLE FOR

Typical Industries

- Aerospace
- Automotive
- Construction
- Glass
- Logistics
- Plastics
- Steel

Suitable Applications

- Castings
- Ductwork
- Engine Servicing
- Glass Handling
- HVAC
- Metalworking
- Sheet Metal Handling

CERTIFICATION



See overleaf for explanation

PRODUCT INFORMATION		
MATERIALS	LINER:	13 gauge HPPE, glass fibre, nylon, spandex
	COATING:	N/A
COLOUR	Grey	
LENGTH (mm)	560	
CUFF STYLE	Elasticated with VELCRO® Brand hook and loop fastener	

- ### RECOMMENDATIONS FOR USE
- **USE:** Cut resistant sleeve. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
 - **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
 - **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
 - **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

ORDERING DETAILS

SIZE	CODE	PACKAGING
22"	SKY1022	10 pairs per bag 120 pairs per case

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance	Circular Blade Cut Resistance	Tear Resistance	Puncture Resistance	Straight Blade Cut Resistance (EN ISO: 13997)	Impact Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

HEAT AND FIRE EN 407

PERFORMANCE LEVELS

0-4	0-4	0-4	0-4	0-4	0-4
Burning Behaviour	Contact Heat Resistance	Convective Heat Resistance	Radiant Heat Resistance	Resistance to Small Drops Of Molten Metal	Resistance to Large Splashes of Molten Metal

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963



EU Type-Examination Certificate issued by SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321)
 The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.