

## Comfort and easy donning for sterile environments

For aseptic applications, AccuTech<sup>®</sup> 91-250 is a thick, clean latex with a hand-specific design for comfort and dexterity. A silicone coating ensures easy donning and double gloving



- Thick latex glove designed for comfort and dexterity
- Compatible with Class 100 (ISO 5) / Grade A Clean Room environments
- Silicone coated for easy donning and double gloving
- Low protein content reduces risk of allergy

### Industries

- Biotechnology Manufacturing
- Laboratory Research and Development
- Pharmaceutical Manufacturing
- Controlled and Critical Environments

### Recommended For

- Aseptic filling and labelling
- Blending, compounding solids and liquids
- Sample taking and processing
- Transferring liquids and solids



## TECHNICAL DATA SHEET

### PRODUCT INFORMATION

	91-250
Material	Natural Rubber Latex
Color	Natural
Shape	Anatomic with Straight Fingers
Cuff	Straight
Manufacturing/QMS Audit Standards	ISO 9001:2015
Regulatory/Standards Compliance	AS/NZS 4179, ASTM D7160, ASTM D3577, CE 0493, EN 420:2003 + A1:2009, EN 556-1:2001, EN ISO 374-1:2016, EN ISO 374-5:2016, EN 374:2003, Please consult the IFU, ISO 10282, ISO 11193, ISO 13485, ISO 14001, ISO 9001
Packaging	1 pair per inner poly pack; 10 inner poly packs per inner polybag; 5 outer polybags per bag; 4 bags per master bag; 1 master bag of 200 pairs per carton/case
Storage	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country of Origin	Malaysia
Available sizes	6.0, 6.5, 7.0, 7.5, 8.0, 8.5, 9.0
Powder Content	Powder-Free
External Glove Surface	Textured Fingers
Sterilization Method	GAMMA irradiation (25 kGy)
Shelf Life	5 years
Tested for use with Chemotherapy Drugs	No
Protein Level	50 µg/g or less of total extractable protein
Anti-static	Not Tested
Vulcanization Chemical Accelerators	<ul style="list-style-type: none"> <li>None</li> </ul>

#### PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/in)	300 / 12		EN 420/ASTM D3767
Freedom from Holes	0.65 AQL		EN 455-1/ASTM D3577
Typical Particle Count ≥0.5µm (counts / cm²)	< 3500		IENT-RP-CC005.4
Minimum Single Wall Palm Thickness (mm/mil)	0.21		EN 420,EN 420/ASTM D3767
Minimum Single Wall Finger Thickness (mm/mil)	0.22		EN 420/ASTM D3767
Minimum Single Wall Cuff Thickness (mm/mil)	0.25		EN 420/ASTM D3767
	Before Ageing	During Ageing	
Ultimate tensile strength (MPa)	24	18	ASTM D412-06a
Force at Break (N)	9	9	EN 455-2

#### ORDERING INFORMATION

	SIZE	6	6.5	7	7.5	8	8.5	9
91-250	REORDER NO.	91250060	91250065	91250070	91250075	91250080	91250085	91250090

For additional information visit us at [www.ansell.com](http://www.ansell.com), or call us at

##### Europe, Middle East & Africa Region

Ansell Healthcare Europe NV  
T: +32 (0) 2 528 74 00  
F: +32 (0) 2 528 74 01

##### Asia Pacific Region

Ansell Global Trading Center  
T: +603 8310 6688  
F: +603 8310 6699

##### North America Region

Ansell Healthcare Products LLC  
US T: +1 800 800 0444  
US F: +1 800 800 0445  
CA T: +1-800-363-8340

##### Latin America & Caribbean Region

Ansell Commercial Mexico S.A. de C.V.  
T: +52 442 248 1544 / 248 3133


##### Australia

Ansell Limited  
T: +61 1800 337 041  
F: +61 1800 803 578

##### UK

Ansell Nitritex  
T: +44 1638 663338  
F: +44 1638 668890

#### Performance Standards and Regulatory Compliance



Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: [www.ansell.com/patentmarking](http://www.ansell.com/patentmarking) © 2020 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.