



TEGERA® 18602

Chemical protection glove, 0,28 mm nitrile, seamless, nylon, diamond grip pattern, Cat. III, green, latex-free, for allround work

PROPERTIES

High level of protection, extra flexible, durable, good grip, extra comfortable

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 7, 8, 9, 10, 11

LINER MATERIAL Seamless, nylon

MATERIAL Nitrile

THICKNESS 0,28 mm

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

LENGTH RANGE 350 mm

COLOUR Green

PAIRS PER PACKAGE/CARTON 6/60

AQL 0.65

DISPLAY Bag OUTER MATERIAL SPECIFICATION Nitrile

SIZE	ART. NO.	EAN NO.
7	18602-7	7340118311982
8	18602-8	7340118303253
9	18602-9	7340118303277
10	18602-10	7340118303215
11	18602-11	7340118303239

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.



CE 0120 Cat. III

 EN 388:2003 2121
  EN 374-2:2003
  EN 374-3:2003 A-JKL
 



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-18

TEGERA® 18602

FEATURES

Protection against chemicals, approved for handling foodstuffs, oil and grease resistant

PREVENTS RISK OF

Corrosive injuries, contact with moisture, contact with damp, contact with oil, contact with oil and fat

PRIMARY ENVIRONMENTS OF USE

Chemical risk environments, microbiological risk environments, environments hazardous to health, corrosive environments, wet environments, oily and greasy environments, dirty environments, harsh environments

PRIMARY AREAS OF USE

Fishing, petro-chemical work, chemical work, laboratory work, paint spraying work, paper industry work, sanitation, cleaning, foodstuff handling, food handling, kitchen work

PRIMARY INDUSTRIES OF USE

Agriculture, oil, gas, petrochemical, food processing, pulp and paper, chemical, automotive

TYPE OF WORK

Medium weight

2(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 18602

EC TYPE EXAMINATION

Notified Body: 0120 SGS United Kingdom, Unit 202B Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom

CHEMICAL RESISTANCE

According to EN 374-3. For details, please contact Ejendals

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

Council directive 89/686/EEC (PPE Directive)

EN 388:2003 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
A) Resistance to abrasion (No. of revolutions)	2	(4)
B) Resistance to cutting (Index)	1	(5)
C) Tear resistance (Newton)	2	(4)
D) Puncturing resistance (Newton)	1	(4)

EN 388 - Testing (specifies the requirements that apply for each safety level).



Level of protection/Performance level	1	2	3	4	5
A) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
B) Resistance to cutting (Index)	1,2	2,5	5,0	10,0	20,0
C) Tear resistance (Newton)	10	25	50	75	
D) Puncturing resistance (Newton)	20	60	100	150	

Suitable for contact with foodstuffs

EN 374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals



CE 0120 Cat. III



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-18

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 18602

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm²/min)

A: Methanol (CAS Number 67-56-1) - Permeation level 4

J: n-Heptane (CAS number 142-85-5) - Permeation level 6

K: Sodium hydroxide 40% (CAS number 1310-73-2) - Permeation level 6

L: Sulphuric acid 96% (CAS number 7664-93-9) - Permeation level 3



CE 0120 Cat. III

EN 388:2003
2121

EN 374-2:2003

EN 374-3:2003
AJKL



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-18

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com