



SIZE	ART. NO.	EAN NO.
8	203-8	7392626040045
9	203-9	7392626040052
10	203-10	7392626040069
11	203-11	7392626040076

TEGERA® 203

Leather glove, winter-lined, 1,0-1,1 mm full grain cowhide, cotton, fleece, Cat. II, black, beige, reinforced fingers and thumb, elasticated 180°, for heavy work

PROPERTIES

Durable, good fit, comfortable, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

PALM MATERIAL Full grain cowhide

PALM THICKNESS 1,0-1,1 mm

BACK MATERIAL Cotton, Full grain cowhide

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 1

CUFF STYLE Safety cuff

CUFF MATERIAL Textile

FASTENING Elasticated 180°

LENGTH RANGE 260-280 mm

COLOUR Black, beige

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag OUTER MATERIAL

SPECIFICATION Leather, cotton, natural latex

INNER MATERIAL SPECIFICATION Polyester

TEGERA® 203

FEATURES

Reinforced index finger, reinforced fingers and thumb

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with cold

PRIMARY ENVIRONMENTS OF USE

Outdoors, cold environments

PRIMARY AREAS OF USE

Building and construction, transport work, machine driving, wood industry work, repair work

PRIMARY INDUSTRIES OF USE

Transportation, building and construction

TYPE OF WORK

Heavy weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3122X



EN 511:2006
12X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-04-03

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 203

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 < 9 kN)

EN 511:2006 Protective gloves against cold



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3122X



EN 511:2006
12X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-04-03

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com