



SIZE	ART. NO.	EAN NO.
7	215-7	7392626014077
8	215-8	7392626014084
9	215-9	7392626014107
10	215-10	7392626014114
11	215-11	7392626014121
12	215-12	7392626035508

TEGERA® 215

Cut resistant glove, fully lined, 0,6-0,7 mm full grain goatskin of top quality, cut resistance level C, KEVLAR® fiber, Cat. II, grey, white, reinforced index finger, reinforced fingertips, elasticated 180°, for precision work

PROPERTIES

High level of protection, extremely good fingertip sensitivity, durable, perfect fit

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 11,8

SIZE RANGE (EU) 7, 8, 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,6-0,7 mm

LINING Fully lined

LINING MATERIAL KEVLAR® fiber

DEXTERITY 5

FASTENING Elasticated 180°

LENGTH RANGE 210-260 mm

COLOUR Grey, white

PAIRS PER PACKAGE/CARTON 12/120

DISPLAY Thread OUTER MATERIAL SPECIFICATION Leather, nylon, natural latex

INNER MATERIAL SPECIFICATION Para-aramid



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X21C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-19

TEGERA® 215

FEATURES

Cut resistant according to 388:2016 level C, reinforced index finger, reinforced fingertips

PREVENTS RISK OF

Cut injuries, abrasion injuries, blisters, grazes, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY AREAS OF USE

Assembly, building and construction, carpentry, installation work, HVAC installation, sheet-metal work, tiling, construction, engineering, transport work, metalwork, glass industry work, wood industry work, repair work

PRIMARY INDUSTRIES OF USE

Glass, bricks, concrete, automotive, transportation, utilities, building and construction

TYPE OF WORK

Light weight

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 215

EU-TYPE EXAMINATION

0493 Centexbel, Technopark 70, BE-9052 Zwijnaarde (Gent) Belgium

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X21C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-03-19

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com