



SIZE	ART. NO.	EAN NO.
9	290-9	7392626060371
10	290-10	7392626060388
11	290-11	7392626060395
12	290-12	7392626060401

TEGERA® 290

Leather glove, half-lined, 0,8-0,9 mm full grain goatskin of top quality, polyester, polypropylene, bamboo, fleece, Cat. II, green high-viz, high-viz colour, wind and waterproof back, water repellent leather, elasticated 180°, for allround work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, very durable, perfect fit, extra comfortable, warm

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 9, 10, 11, 12

PALM MATERIAL Full grain goatskin of top quality

PALM THICKNESS 0,8-0,9 mm

BACK MATERIAL Polyester, Polypropylene

LINING Half-lined

LINING MATERIAL Bamboo, Fleece

DEXTERITY 5

FASTENING Elasticated 180°

COLOUR Green high-viz

PAIRS PER PACKAGE/CARTON 6/60

DISPLAY Hook with hangtag OUTER MATERIAL

SPECIFICATION Leather, polyester, natural latex

INNER MATERIAL SPECIFICATION Viscose

1(3)

TEGERA® 290

FEATURES

High-viz colour, reinforced fingers and thumb, water repellent palm, wind and waterproof back

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with damp

PRIMARY ENVIRONMENTS OF USE

Windy environments, all-year use, moist environments, harsh environments

PRIMARY AREAS OF USE

Machine operating, building and construction, carpentry, installation work, HVAC installation, tiling, construction, soil preparation, transport work, machine driving, airport work, wood industry work, forest work, agricultural work, gardening, repair work

PRIMARY INDUSTRIES OF USE

Transportation, utilities, building and construction, logistics, service, retail

TYPE OF WORK

Medium weight

2(3)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2111X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-04-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 290

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2111X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-04-15

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com