



CRF®

SIZE	ART. NO.	EAN NO.
6	432-6	7340118320403
7	432-7	7340118320410
8	432-8	7340118320427
9	432-9	7340118320434
10	432-10	7340118320380
11	432-11	7340118320397
5	432-5	7340118329857

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 432

Cut resistant glove, PU, palm-dipped, CRF® Technology, Lycra®, polyester, 13 gg, smooth finish, cut resistance level B, Cat. II, white, breathable back, water and oil repellent palm, for fine assembly work

PROPERTIES

Flexible, good grip, comfortable

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level B

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 6,5

SIZE RANGE (EU) 5, 6, 7, 8, 9, 10, 11

LINER MATERIAL CRF® Technology, Lycra®, polyester, 13 gg

DIPPING Palm-dipped

DIPPING MATERIAL PU

DEXTERITY 5

GRIP PATTERN Smooth finish

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 220-270mm

COLOUR White

PAIRS PER PACKAGE/CARTON 12/60

PIECES PER BOX 12

DISPLAY Bulk pack

MATERIAL SPECIFICATION Polyurethane, HPPE, polyester, elastane

TEGERA® 432

FEATURES

Cut resistant according to 388:2016 level B

PREVENTS RISK OF

Cut injuries, scratches, lacerations

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, clean environments

PRIMARY AREAS OF USE

Fine assembly, assembly, inspection work, machine operating, installation work, warehouse work

PRIMARY INDUSTRIES OF USE

Pulp and paper, rubber and plastic, metal fabrication, machinery and equipment, MRO, logistics

TYPE OF WORK

Light weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X42B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

2(3)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 432

EU-TYPE EXAMINATION

0075 CTC, 4 rue Hermann Frenkel, 69367 Lyon Cedex 07
France

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	4	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	B	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
4X42B



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com