



TEGERA® 464

Heat-resistant glove, nitrile, cotton, Cat. II, grey, withstands contact heat up to 250°C, extra long, for heavy work

PROPERTIES

High level of protection

SPECIFICATION

TYPE OF GLOVE Heat protection gloves

CATEGORY Cat. II

SIZE RANGE (EU) 9, 10, 11

LINER MATERIAL Cotton

MATERIAL Nitrile

DEXTERITY 4

CUFF STYLE Extended safety cuff

CUFF MATERIAL Textile

LENGTH RANGE 350 mm

COLOUR Grey

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 6

DISPLAY Bulk pack

MATERIAL SPECIFICATION Cotton, polyester, nitrile

SIZE	ART. NO.	EAN NO.
11	464-11	7392626032347
9	464-9	7392626059788
10	464-10	7392626059795

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 464

PREVENTS RISK OF

Burn injuries, heat injuries

PRIMARY AREAS OF USE

Sheet-metal work, metalwork, hot work, glass industry work, kitchen work, hotel- and restaurant work

PRIMARY INDUSTRIES OF USE

Rubber and plastic, glass, bricks, concrete, metal fabrication, HoReCa

TYPE OF WORK

Heavy weight

2(3)

CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3232X



EN 407:2004
X2XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 464

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
3232X



EN 407:2004
X2XXXX



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com