TEGERA®

TEGERA® 57

Leather glove, winter-lined, 1,0-1,2 mm full grain oxhide, cotton, fleece, Cat. II, grey, white, reinforced index finger, reinforced fingers and thumb, for heavy work

PROPERTIES

High level of protection, durable, good grip, good fit, comfortable, warm

SPECIFICATION

TYPE OF GLOVE Cold insulation gloves

CATEGORY Cat. II

SIZE RANGE (EU) 8, 10, 11

PALM MATERIAL Full grain oxhide

PALM THICKNESS 1,0-1,2 mm

BACK MATERIAL Cotton

LINING Winter-lined

LINING MATERIAL Fleece

DEXTERITY 5

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

LENGTH RANGE 255-270 mm

COLOUR Grey, white

PAIRS PER PACKAGE/CARTON 6/60

PIECES PER BOX 6

DISPLAY Bulk pack OUTER MATERIAL SPECIFICATION Leather, cotton, natural latex

INNER MATERIAL SPECIFICATION Acrylic

SIZE	ART. NO.	EAN NO.
8	57-8	7392626005778
10	57-10	7392626005792
11	57-11	7392626017238

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 57

FEATURES
Reinforced index finger, reinforced fingers and thumb

PREVENTS RISK OF
Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt, contact with cold

PRIMARY ENVIRONMENTS OF USE
Outdoors, cold environments

PRIMARY AREAS OF USE
Building and construction, construction, soil preparation, engineering, transport work, machine driving, metalwork, mining, wood industry work, repair work

PRIMARY INDUSTRIES OF USE
Mining, transportation

TYPE OF WORK
Heavy weight

CE Cat. II

EN 420:2003 + A1:2009

EN 388:2016 2222X

EN 511:2006 11X

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com

TEGERA®

TEGERA® 57

Cat. II

EN 420:2003 + A1:2009 | EN 388:2016 2222X | EN 511:2006 11X

EU-TYPE EXAMINATION

0493 Centexbel, Technologiepark 70, BE-9052 Zwijnaarde (Gent) Belgium

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	2	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	2	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing
(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 511:2006 Protective gloves against cold

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB
Box 7, SE-793 21 Leksand, Sweden
Phone +46 (0) 247 360 00
Fax +46 (0) 247 360 10
info@ejendals.com
order@ejendals.com
www.ejendals.com