



SIZE	ART. NO.	EAN NO.
7	629-7	7392626064461
8	629-8	7392626064478
9	629-9	7392626064485
10	629-10	7392626064492
11	629-11	7392626064508

TEGERA® 629

Cut resistant glove, latex, 3/4 dipped, Dyneema®, glass fibre thread, nylon, 10 gg, granulated, cut resistance level C, Cat. II, black, grey, waterproof palm, Velcro®, for assembly work

PROPERTIES

High level of protection, good fingertip sensitivity, flexible, durable, good grip, good fit, comfortable, light

SPECIFICATION

TYPE OF GLOVE Cut resistant gloves

CATEGORY Cat. II

CUT RESISTANCE (EN ISO 13997) Cut resistance level C

CUT RESISTANCE (EN ISO 13997) NEWTON VALUE 10,7

SIZE RANGE (EU) 7, 8, 9, 10, 11

LINER MATERIAL Dyneema®, glass fibre thread, nylon, 10 gg

DIPPING 3/4 dipped

DIPPING MATERIAL Latex

DEXTERITY 5

GRIP PATTERN Granulated

FASTENING Velcro®

LENGTH RANGE 220 - 260mm

COLOUR Black, grey

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 12

DISPLAY Bag with euro slot

MATERIAL SPECIFICATION Natural latex, UHMWPE, nylon, glass fibre thread

TEGERA® 629

FEATURES

Cut resistant according to 388:2016 level C, water repellent palm

PREVENTS RISK OF

Cut injuries, abrasion injuries, grazes, scratches, lacerations, contact with dirt, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Cut risk environments, slippery environments, wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Building and construction, installation work, tiling, concrete work, engineering, metalwork, glass industry work, forest work, agricultural work, repair work

PRIMARY INDUSTRIES OF USE

Agriculture, mining, pulp and paper, glass, bricks, concrete, metal fabrication, machinery and equipment, MRO, automotive, transportation, utilities, building and construction

TYPE OF WORK

Medium weight

2(3)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X43C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 629

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	X	(5)
c) Tear resistance (N)	4	(4)
d) Puncturing resistance (N)	3	(4)
e) Cut resistance, EN ISO 13997 (N)	C	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2X43C



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com