

TEGERA® 680

Leather glove, unlined, 0,7-0,9 mm full grain goatskin, cotton, Cat. II, grey, white, reinforced index finger, reinforced fingers and thumb, elasticated 180°, for allround work

PROPERTIES

High level of protection

SPECIFICATION

TYPE OF GLOVE Work gloves - General handling

CATEGORY Cat. II

SIZE RANGE (EU) 8, 9, 10, 11

PALM MATERIAL Full grain goatskin

PALM THICKNESS 0,7-0,9 mm

BACK MATERIAL Cotton

LINING Unlined

DEXTERITY 5

CUFF STYLE Safety cuff

CUFF MATERIAL Textile

FASTENING Elasticated 180°

LENGTH RANGE 245-280 mm

COLOUR Grey, white

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 12

DISPLAY Thread

MATERIAL SPECIFICATION Leather, cotton, natural latex



SIZE	ART. NO.	EAN NO.
9	680-9	7392626017382
10	680-10	7392626068001
11	680-11	7392626068018
8	680-8	7392626068087

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 680

FEATURES

Reinforced index finger, reinforced fingers and thumb

PREVENTS RISK OF

Abrasion injuries, blisters, grazes, scratches, lacerations, contact with dirt

PRIMARY ENVIRONMENTS OF USE

Harsh environments

PRIMARY AREAS OF USE

Building and construction, construction, soil preparation, transport work, machine driving, airport work, wood industry work

PRIMARY INDUSTRIES OF USE

Mining, transportation, utilities, building and construction

TYPE OF WORK

Medium weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 680

EU-TYPE EXAMINATION

0493 Centexbel, Technologiepark 70, BE-9052 Zwijnaarde (Gent) Belgium

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	2	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	2	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
2121X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com