



TEGERA® 767

Textile glove, unlined, jersey, cotton, Cat. II, blue, soft, elasticated 360°, for allround work

PROPERTIES

Good fit

SPECIFICATION

TYPE OF GLOVE Gloves for general use, minimal risks

CATEGORY Cat. II

SIZE RANGE (EU) 8, 10

PALM MATERIAL Jersey, Cotton

BACK MATERIAL Jersey

LINING Unlined

DEXTERITY 3

CUFF STYLE Knitwrist cuff

CUFF MATERIAL Textile

FASTENING Elasticated 360°

COLOUR Blue

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 12

DISPLAY Bulk pack

MATERIAL SPECIFICATION Cotton, polyester OUTER

MATERIAL SPECIFICATION Cotton, polyester

SIZE	ART. NO.	EAN NO.
8	767-8	7392626076778
10	767-10	7392626076792

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 767

FEATURES

Chain stitch, soft

PREVENTS RISK OF

Blisters, grazes

PRIMARY ENVIRONMENTS OF USE

Dry environments

PRIMARY AREAS OF USE

Painting, warehouse work, gardening, sanitation, service work

PRIMARY INDUSTRIES OF USE

Service

TYPE OF WORK

Medium weight



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
0110X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 767

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	0	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	0	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 - Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2 000	8 000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)



CE Cat. II

EN 420:2003
+ A1:2009



EN 388:2016
0110X



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-14

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com