



TEGERA® 8140

Chemical protection glove, 0,38 mm latex, diamond grip pattern, flock-lined, Cat. III, blue, for allround work

PROPERTIES

Extra flexible, good fit, comfortable

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 6, 7, 8, 9, 10

MATERIAL Latex

THICKNESS 0,38 mm

INSIDE Flock-lined

DEXTERITY 5

GRIP PATTERN Diamond grip pattern

LENGTH RANGE 300 mm

COLOUR Blue

PAIRS PER PACKAGE/CARTON 12/144

PIECES PER BOX 0

AQL 1.5

DISPLAY Bag with euro slot

SIZE	ART. NO.	EAN NO.
6	8140-6	7392626007604
7	8140-7	7392626007611
8	8140-8	7392626007628
9	8140-9	7392626007635
10	8140-10	7392626007642

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8140

FEATURES

Splash protection against chemicals

PREVENTS RISK OF

Contact with dirt, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Fishing industry work, fishing, decontamination, sanitation, cleaning, foodstuff handling, food handling, kitchen work, care work, service work

PRIMARY INDUSTRIES OF USE

Agriculture, food processing, service

TYPE OF WORK

Medium weight

CE 0598 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 1010X  EN ISO 374-1:2016/Type B AKLMNPST

 EN ISO 374-5:2016   

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-24

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8140

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	1	(4)
b) Cut resistance (Index)	0	(5)
c) Tear resistance (N)	1	(4)
d) Puncturing resistance (N)	0	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

Suitable for contact with foodstuffs

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and microorganisms – Part 5 Terminology and performance requirements for microorganism risks.

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0598 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 1010X  EN ISO 374-1:2016/Type B AKLMNPST

 EN ISO 374-5:2016   

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-24

TEGERA® 8140

EN ISO 374-1:2016/Type B Protective gloves against dangerous chemicals and microorganisms – Part 1: Terminology and performance requirements for chemical risks.

Test according to EN ISO 374-1:2016

Tested chemical	A	K	L	M	N	P	S	T
Permeation level	1	6	2	4	1	4	5	6
Degradation %	22,3	-26,8	49,8	24,7	-16,9	X	-16,5	

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm²/min)

K: Sodium hydroxide 40% (CAS number 1310-73-2)

L: Sulphuric acid 96% (CAS number 7664-93-9)

M: Nitric acid 65% (CAS number 7697-37-2)

P: Hydrogen peroxide 30% (CAS number 7722-84-1)

T: Formaldehyde 37% (CAS number 50-00-0)



CE 0598 Cat. III

EN 420:2003 + A1:2009  EN 388:2016 1010X  EN ISO 374-1:2016/Type B AKLMNPST

 EN ISO 374-5:2016   

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-24

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com