



TEGERA® 8160

Chemical protection glove, 0,5* mm (*chem-layer) latex, fully dipped, double-dipped, interlock, foam grip pattern, Cat. III, blue, waterproof, for allround work

PROPERTIES

High level of protection, flexible, good grip, comfortable, warm

SPECIFICATION

TYPE OF GLOVE Disposable and/or chemical resistant gloves

CATEGORY Cat. III

SIZE RANGE (EU) 6, 7, 8, 9, 10, 11

LINER MATERIAL Interlock

DIPPING Fully dipped, double-dipped

DIPPING MATERIAL Latex

THICKNESS 0,5* mm (*chem-layer)

GRIP PATTERN Foam grip pattern

LENGTH RANGE 300 mm

COLOUR Blue

PAIRS PER PACKAGE/CARTON 12/120

PIECES PER BOX 0

DISPLAY Bag with euro slot OUTER MATERIAL SPECIFICATION Natural latex

INNER MATERIAL SPECIFICATION Cotton

ANTIBACTERIAL/BIOCIDAL TREATMENT Pyrithione zinc (CAS number 13463-41-7)

SIZE	ART. NO.	EAN NO.
7	8160-7	7392626007543
8	8160-8	7392626007550
9	8160-9	7392626007567
10	8160-10	7392626007574
11	8160-11	7392626007581
6	8160-6	7392626008038

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

TEGERA® 8160

PREVENTS RISK OF

Contact with dirt, contact with moisture, contact with damp

PRIMARY ENVIRONMENTS OF USE

Cold environments, warm environments, wet environments, moist environments, dirty environments

PRIMARY AREAS OF USE

Building and construction, painting, concrete work, glass industry work, agricultural work, marine work, fishing industry work, fishing, petro-chemical work, chemical work, chemical technology work, paint spraying work, paper industry work, decontamination, sanitation, cleaning

PRIMARY INDUSTRIES OF USE

Agriculture, building and construction

TYPE OF WORK

Medium weight

2(4)

CE 0598 Cat. III

EN 420:2003
+ A1:2009



EN 388:2016
3131X



EN 407:2004
X2XXXX



EN ISO 374-1:2016/Type B
AKLPT



EN ISO 374-5:2016



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-24

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com

TEGERA® 8160

EU-TYPE EXAMINATION

2777 Satra Technology Europe Ltd Bracetown Business Park, Clonee, Dublin 15, Dublin, Ireland

CHEMICAL RESISTANCE

According to EN16523-1:2015. For details, please contact Ejendals.

COMPLIANCE DESCRIPTION

EN 420:2003 + A1:2009 Protective gloves - general requirements and test methods

EU 2016/425

EN 388:2016 Protective gloves against mechanical risks

Property	Level Achieved	(Maximum Performance)
a) Resistance to abrasion (No. of revolutions)	3	(4)
b) Cut resistance (Index)	1	(5)
c) Tear resistance (N)	3	(4)
d) Puncturing resistance (N)	1	(4)
e) Cut resistance, EN ISO 13997 (N)	X	(F)
f) Impact protection, EN 13594:2015		(P)

EN 388 – Testing

(specifies the requirements that apply for each safety level).

Level of protection/Performance level	1	2	3	4	5
a) Resistance to abrasion (No. of revolutions)	100	500	2000	8000	
b) Cut resistance (Index)	1,2	2,5	5,0	10,0	20,0
c) Tear resistance (N)	10	25	50	75	
d) Puncturing resistance (N)	20	60	100	150	

Level of protection/Performance level	A	B	C	D	E	F
e) Cut resistance, EN ISO 13997 (N)	2	5	10	15	22	30

Level of protection/Performance level	P
f) Impact protection, EN 13594:2015	Pass (Level 1 ≤ 9 kN)

EN 407:2004 Protective gloves against thermal risks (heat and/or fire)

EN ISO 374-5:2016 Protective gloves against dangerous chemicals and microorganisms – Part 5 Terminology and

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com



CE 0598 Cat. III

EN 420:2003 + A1:2009



EN 388:2016 3131X



EN 407:2004 X2XXXX



EN ISO 374-1:2016/Type B AKLPT



EN ISO 374-5:2016



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-24

TEGERA® 8160

performance requirements for microorganism risks.

EN ISO 374-1:2016/Type B Protective gloves against dangerous chemicals and microorganisms – Part 1: Terminology and performance requirements for chemical risks.

Test according to EN ISO 374-1:2016

Tested chemical	A	K	L	P	T
Permeation level	2	2	3	5	6
Degradation %	-2,8	-7,7	55,7	-4,6	-21,9

Permeation levels are based on breakthrough times as follows

Permeation level	1	2	3	4	5	6
Minimum breakthrough times (min)	10	30	60	120	240	480

Definition of breakthrough time through the glove palm (1ugm/cm²/min)

A: Methanol (CAS Number 67-56-1)

K: Sodium hydroxide 40% (CAS number 1310-73-2)

L: Sulphuric acid 96% (CAS number 7664-93-9)

P: Hydrogen peroxide 30% (CAS number 7722-84-1)

T: Formaldehyde 37% (CAS number 50-00-0)



CE 0598 Cat. III

EN 420:2003
+ A1:2009



EN 388:2016
3131X



EN 407:2004
X2XXXX



EN ISO 374-1:2016/Type B
AKLPT



EN ISO 374-5:2016



All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

2020-06-24

4(4)

ejendals
PROTECTING HANDS AND FEET

EJENDALS AB

Box 7, SE-793 21 Leksand, Sweden

Phone +46 (0) 247 360 00

Fax +46 (0) 247 360 10

info@ejendals.com

order@ejendals.com

www.ejendals.com