

TECHNICAL DATA SHEET

POWERFORM® S8+ TRACTEK[™] HIGH PERFORMANCE GRIP NITRILE GLOVES

PRODUCT DESCRIPTION

SPECIFICATIONS							
PRODUCT:		PowerForm S8+					
GRADE:		Powder-Free Industrial					
MATERIAL:		Nitrile					
THICKNESS	Finger:	7.0mil	0.18mm				
	Palm:	5.5mil	0.14mm				
	Cuff:	4.5mil	0.11mm				
COLOR	Outer:	Green					
	Inner:	Yellow					
SURFACE	Outer:	Fully Textured					
	Inner:	Smooth					
LENGTH:		11.0"	280mm				
WEIGHT*:		9.8g					
FIT TYPE:		Ambidextrous					
CUFF TYPE:		Beaded					
WATERTIGHT AQL:		1.5					
ORIGIN COUNTRY:		China					

PHYSICAL PROPERTIES							
	PRE-AGING	POST-AGING					
TENSILE STRENGTH:	21 MPa	19 MPa					
ELONGATION:	560%	550%					
FORCE AT BREAK:							

INTEGRATED TECHNOLOGIES

- TouchTekTM protects skin and prevents contamination.
- MilTek® offers durability and tactile sensitivity.
- TracTekTM is a high density pattern designed to maximize grip in wet or oily conditions.





Waste Management

Fabrication

Assembly

Maintenance

*Specification based on size medium gloves

STANDARDS & CERTIFICATIONS

Please visit swsafety.com/symbols for information on standards used on this document.

ORDERING

ITEM NO.	SIZE		PALM	WIDTH	PACKAGING	
N807712	S	6.5-7	3.7"	95mm	50 gloves per box	10 boxes per case
N807713	Μ	7.5-8	3.9"	100mm	50 gloves per box	10 boxes per case
N807714	L	8.5-9	4.1"	104mm	50 gloves per box	10 boxes per case
N807715	XL	9.5-10	4.5"	114mm	50 gloves per box	10 boxes per case
N807716	XXL	10.5-11	4.9"	124mm	50 gloves per box	10 boxes per case
N807717	XXXL	11.5-12	5.2"	133mm	50 gloves per box	10 boxes per case

PUNCTURE

APPLICATIONS

- Food Handling and Packaging
- Light Machining Operations
- Chemical Handling
- Liquid Handling
- Painting
- Janitorial Maintenance
- Oily or Wet Surfaces

STORAGE

Keep out of sunlight. Store in a cool, dry place. Keep away from sources of ozone or ignition.



SWSAFETY.COM

©2017 SW Safety Solutions Inc. All rights reserved. Trademarks and Registered Trademarks are the property of SW Safety Solutions Inc. and its affiliates. SW Products are protected by U.S. and foreign patents and patents pending.

SW SAFETY SOLUTIONS INC. T: +1-510-429-8692 | F: +1-510-487-5347



APPROVED

For Industrial Use