CUT RESISTANT GLOVES

2023-02-06

PROBABLY THE THINNEST CUT F GLOVE YET

Cnff (2)

<u>Nedela</u>

Probably the thinnest cut F glove on the market, made with the new advanced CRF®Omni technology, nylon and elastane. 18 gg knitted glove and PU-dipped, superior for any work with very sharp and small objects. Reinforcement between the thumb and index finger and touchscreen functionality. The new CRF® Omni technology does not contain any steel or glass fiber that can irritate the skin. The gloves stay soft and comfortable throughout the work task.

CHARACTERISTICS

TEGERA® 8845

- Highest level of protection
- Good grip
- Extremely good fingertip sensitivity
- Extra flexible

FUNCTIONS

For touchscreen

All values for the specified product are indicated without tolerances and may vary to actual

value for individual products. We reserve the right to modify or update the information in this

document without prior notice

- Soft
- Reinforcement between index finger
 and thumb

Extremely thin and soft with touch, superior for any work with sharp and small objects.





TEGERA® 8845

| | COMPLIANCE | | | |
|--|--|------------------|---------------------------------|--|
| PREVENTS RISK OF | (| | EAC | |
| cut injuries, abrasion injuries, scratches, lacerations, | | CA | LIIL | |
| contact with dirt, contact with moisture | TP TC 019:2011 | i Informa | tion/UIS EN 388:2016+A1:2018 | |
| PRIMARY ENVIRONMENTS OF USE | | | 3X43F | |
| cut risk environments, dry environments, moist | EN ISO 21420:2020 | ANSI | ANSI | |
| environments, dirty environments | | A7 | 3 | |
| PRIMARY AREAS OF USE | | CUT | ABR | |
| assembly, building and construction, metalwork, paper | FEATURES | | | |
| industry work, sheet-metal work | Cut protection | For touchscreen | | |
| PRIMARY INDUSTRIES OF USE | - | V | | |
| pulp and paper, metal fabrication, automotive | | | | |
| TYPE OF WORK | | | | |
| Medium weight | | | | |
| SPECIFICATION | | | | |
| TYPE Cut resistant gloves | | | | |
| CATEGORY Cat. II LINING MATERIAL 1 8 gg, CRF[®] Omni Technology, Nylon , | | | | |
| Spandex | | | | |
| LENGTH 210-270 mm | | | | |
| GRIP DESIGN Smooth finish | | | | |
| COLOUR Black, Green, Grey | | | | |
| PAIRS PER: BUNDLE/CARTON 6/120 | | | | |
| DISPLAY TYPE Bulk pack | | | | |
| DIPPING Palm-dipped DIPPING MATERIAL PU | | I | | |
| CUFF STYLE Knitwrist cuff | SIZE | ARTICLE | EAN | |
| CUFF MATERIAL Textile | SIZE | NUMBER | EAN | |
| CUT RESISTANCE (EN ISO 13997) Cut resistance level F | 5 | 8845-5 | 7340118412597 | |
| CUT RESISTANCE (EN ISO 13997) TDM: 35.3 N | 6 | 8845-6 | 7340118412740 | |
| INNER MATERIAL SPECIFICATION HPPE (High | | _ | | |
| performance polyethylene), Nylon, Tungsten fibre thread, | 7 | 8845-7 | 7340118412894 | |
| Elastane OUTER MATERIAL SPECIFICATION Polyurethane | 8 | 8845-8 | 7340118413044 | |
| of terminal ende of control of organization | 9 | 8845-9 | 7340118413198 | |
| | 10 | 8845-10 | 7340118413341 | |

11

8845-11



Limavägen 28, SE-793 32 Leksand, Sweden

7340118413495

Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com